







JETTING MACHINE OVERVIEW

| | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------|----------------------|-------------------------------|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|-------------------|---|----|----|----|----|----|----|----|----------------------|-------------------------------------|----|----|----|----|----|----|----|----|----|----|----|----|---------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|-------|----------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|------------------|-----------------------|--|--|--|--|--|--|--|----------------|---|--|--|--|--|--|--|--|
| | 0.8 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 59 | 60 | 61 | 62 | 63 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING TRIGGAIR | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | FTTH | | | | | | | | | | | | | | | | BLOWING DISTANCE | 500 m+ (1640 feet+) | | | | | | | | AIR CONNECTION | Std 3/8" Cejn | | | | | | | |
| | MAX SPEED | 150 m/min (492 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 8-16 Bar (120-230 psi) | | | | | | | | COMPRESSOR AIRFLOW | 100-150 L /min. (3.5- 7.0 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 0.8 – 3 mm | | | | | | | | | | | | | | | | WxHxD (HARD CASE) | 460 x 370 x 180 mm (18.1x13.8x7.1 in.) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 3, 5, 7, 8 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 2,3 kg (13,9 lb) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 30 N (Up to 6.74 lbf) | | | | | | | | | | | | | | | | BATTERY | 12V, 4Ah Milwaukee | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING VO | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | FTTH | | | | | | | | | | | | | | | | BLOWING DISTANCE | 1000 m+ (3280 feet+) | | | | | | | | AIR CONNECTION | Std 3/8" Cejn | | | | | | | |
| | MAX SPEED | 250 m/min (820 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 8-16 Bar (120-230 psi) | | | | | | | | WORKS WITH JETLOGGER | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 0.8 – 6.0 mm | | | | | | | | | | | | | | | | WxHxD (HARD CASE) | 600x500x300 mm (4.72x8.66x6.69 inches) | | | | | | | | COMPRESSOR AIRFLOW | 100-600 L /min. (3.5- 21 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 3 – 16 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 13 kg (4.4 lb) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 60 N (Up to 13.5 lbf) | | | | | | | | | | | | | | | | BATTERY | 18 V, 5Ah Milwaukee | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING VO HD | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | FTTH | | | | | | | | | | | | | | | | BLOWING DISTANCE | 1500 m + (4900 feet+) | | | | | | | | AIR CONNECTION | Std 3/8" Cejn | | | | | | | |
| | MAX SPEED | 110 m/min (361 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 8-16 Bar (120-230 psi) | | | | | | | | WORKS WITH JETLOGGER | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 0.8 – 6.5 mm | | | | | | | | | | | | | | | | WxHxD (HARD CASE) | 600 x 500 x 300 mm (4.72x8.66x6.69 in.) | | | | | | | | COMPRESSOR AIRFLOW | 100-600 L /min. (3.5- 21 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 3 – 16 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 13 kg (4.4 lb) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 200 N (Up to 45 lbf) | | | | | | | | | | | | | | | | BATTERY | 18 V, 5Ah Milwaukee | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING V2 | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | Distribution Network | | | | | | | | | | | | | | | | BLOWING DISTANCE | 3000 m+ (9842 ft+) | | | | | | | | FLOATING | <input checked="" type="checkbox"/> | | | | | | | |
| | MAX SPEED | 200 m/min (656 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 10-16 Bar (145-230 psi) | | | | | | | | WORKS WITH JETLOGGER | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 2.4 – 16 mm | | | | | | | | | | | | | | | | WxHxD | 360 x 230 x 410 mm (16.5x9.1x17.7 in.) | | | | | | | | COMPRESSOR AIRFLOW | 500-10000 L/min. (17- 353 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 7 – 50 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 10,5 kg (23 lb) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 550 N (Up to 123.5 lbf) | | | | | | | | | | | | | | | | AIR CONNECTION | 3/4" Claw connector | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING V3 1800 N | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | Distribution Network | | | | | | | | | | | | | | | | BLOWING DISTANCE | 5000 m+ (16 500 ft+) | | | | | | | | FLOATING | <input checked="" type="checkbox"/> | | | | | | | |
| | MAX SPEED | 50 m/min (165 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 10-16 Bar (145 / 230 psi) | | | | | | | | SUBDUCTING | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 4 – 40 mm | | | | | | | | | | | | | | | | WxHxD | 700 x 400 x 590 mm (27.6x15.8x23.2 in.) | | | | | | | | RODPUSH | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 10 – 63 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 25 kg (55 lb) | | | | | | | | WORKS WITH JETLOGGER | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 1800 N (Up to 400 lbf) | | | | | | | | | | | | | | | | AIR CONNECTION | 1" Claw connector | | | | | | | | COMPRESSOR AIRFLOW | 1000-12000 L/min. (35- 423 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| JETTING V4 GRIZZON | CABLE DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | DUCT DIAMETER IN MM | | | | | | | | | | | | | | | | | | | | | | | |  | USAGE | Distribution Network | | | | | | | | | | | | | | | | BLOWING DISTANCE | 5000 m+ (16 500 ft+) | | | | | | | | FLOATING | <input checked="" type="checkbox"/> DUAL GEAR <input checked="" type="checkbox"/> | | | | | | | |
| | MAX SPEED | 110 m/min (361 ft/min) | | | | | | | | | | | | | | | | MIN/MAX PRESSURE | 10-16 Bar (145 / 230 psi) | | | | | | | | SUBDUCTING | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | CABLE DIAMETER | 4 – 40 mm | | | | | | | | | | | | | | | | WxHxD | 710 x 340 x 540 mm (28.0 x 13.4 x 21.3 in.) | | | | | | | | RODPUSH | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | DUCT DIAMETER | 10 – 63 mm | | | | | | | | | | | | | | | | WEIGHT | Approx 31 kg (68 lb) | | | | | | | | WORKS WITH JETLOGGER | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | PUSHING FORCE | Up to 2000 N (Up to 450 lbf) | | | | | | | | | | | | | | | | AIR CONNECTION | 1" Claw connector | | | | | | | | COMPRESSOR AIRFLOW | 1000-12000 L/min. (35- 423 cfm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |